

The Mohawk Group

NuBroadlok™ Latex Carpet Edge Sealer is a **natural latex adhesive** designed for sealing raw carpet edges, replacing damaged or burned nap, strengthening worn backings and joining padding. NuBroadlok™ Edge Sealer is extremely fast drying, easy spreading, and non-flammable. Bonding strength increases with age and will not deteriorate after shampooing.

NuBroadlok™ Latex Carpet Edge Sealer is recommended for seaming polypropylene, jute, latex unitary and woven backed carpets - Prevents unraveling of carpet edges and/or delamination of carpet backings and yarns – For binding, sealing raw edges and applying new backings to area rugs.

Features:

- **CRI Green Label Plus Approved**
- **Non-flammable**
- **Fast Dry – High Strength**
- **Water Cleanup**
- **For Most Carpet Backing**

NU BROADLOK™ LATEX CARPET EDGE SEALER IS NOT RECOMMENDED FOR SEAMING URETHANE, VINYL BACKED CARPETS OR SHEETGOODS.

Handling and Use: This product is made of natural latex and contains ammonia. Implement effective ventilation and/or air movers before, during and after installation to provide adequate air circulation and to enhance the curing time of the sealer. Do not use this product in occupied spaces. Avoid skin and eye contact.

Preparation & Application:

- NuBroadlok™ Latex Carpet Edge Sealer is **NOT** freeze-thaw stable. Do not allow the adhesive to freeze.
- NuBroadlok™ Latex Carpet Edge Sealer and substrate must be at least 65°F (18.3°C) or higher.
- Prepare and cut the carpet edges according to The Mohawk Group's recommendations.

Application:

- Apply a 1/8" bead of adhesive to **BOTH** sides of the carpet along the trimmed edge of carpet. Smooth out any excess adhesive being careful not to get any adhesive on the carpet nap.
- As an edge sealer, allow the adhesive on both edges of the carpet to become dry to the touch before joining the seam.

Cleanup: Do not allow adhesive to dry on carpet nap. Adhesive must be removed while it is still wet. Use warm, soapy water to remove any traces of sealer on the carpet surface and wipe clean all seams to ensure that there is no excess sealer left on the face of the yarn that can eventually attract dirt.

Coverage: NuBroadlok™ Latex Carpet Edge Sealer 1 qt. (946mL) container covers approximately 800 linear feet.

Warranty: Buyer assumes all risk of use, handling and storage of product not in strict accordance with label directions. No express warranties are given. Any implied warranty of merchantability of fitness for particular use is limited to one year from date of purchase. Liability for any incidental or consequential damage or loss is specifically excluded at all times. If used for other than professional purposes, any implied warranty of merchantability or fitness for particular use is excluded.

First Aid: This product is made from natural latex. Workers exposed to natural latex may develop allergic reactions.

Skin Contact: Remove fresh adhesive with warm water and soap. Consult physician if irritation develops.

Eye Contact: Flood with large quantities of water for 15 minutes. See physician if irritation develops.

Ingestion: Do not induce vomiting. If victim is conscious, give water to dilute. Contact a physician immediately.

KEEP OUT OF REACH OF CHILDREN

10/06/08