

The Mohawk Group

NuBroadlok™ Premium Multi-Purpose Adhesive

For Mohawk Group - Lees, Karastan Contract, Bigelow Commercial and Durkan

The Mohawk Group NuBroadlok™ Premium Multi-Purpose Adhesive is a fast-grabbing, high solids, commercial carpet adhesive for use with all Mohawk broadloom carpets with the exception of Lees Unibond or U2. NuBroadlok™ is the perfect choice for heavy duty installations. This low odor adhesive provides quick tack as well as excellent re-tack properties. NuBroadlok™ is CRI Green Label Plus approved.

Installation Instructions: The floor must be sound, smooth, dry and clean. Remove any dirt, wax, loose paint, and foreign material that would interfere with a good bond. Seal porous or dusty concrete surfaces with Mohawk PrimeCoat or Mohawk appropriate sealer. When installing over a non-porous surface, let adhesive become tacky (1" – 2" legs when finger tested).

Substrates & Site Conditions: Apply NuBroadlok™ over smooth above, on or below grade concrete, APA grade underlayment plywood, Terrazzo, polymer-fortified Portland cement underlayment, and existing well bonded resilient flooring which has been properly prepared. Existing adhesives must be scraped down to a smooth residue. Calcium Chloride (ASTM F1869) test results must not exceed 5 lbs., in-situ relative humidity readings (ASTM F2170) must not exceed 80%, and pH must be between 5.0 and 9.0. Do not use on chemically cleaned subfloors.

Site conditions, floor preparations, moisture, and alkalinity requirements should comply with those specified by the Carpet and Rug Institute. The installation site must be acclimated with HVAC in operation. The floor and room temperature, as well as flooring materials and adhesive, must be maintained at 65°- 95° F, and the humidity below 65% for 48 hours prior to, during, and after the testing and installation.

Floorcoverings: Use NuBroadlok™ to install all Mohawk backings with the exception of Lees Unibond or U2. Not for use on PVC back floor coverings.

Open Time: 20 to 30 minutes under normal conditions. High humidity and cold, and sealed or impervious substrates will extend open times.

Trowel Sizes:

TMG woven backings:

1/8" x 1/8" x 1/16" V-notched trowel 8 – 10 yds.² /gallon

TMG other backings:

1/8" x 1/8" x 1/8" U-notched trowel 6 - 10 yds.²/gallon

Shelf Life: 1 year from manufacturing date, in an unopened container.

This product is not photochemically reactive as defined by California Rules 102 and 443.

VOC content is below that established by the California SCAQMD Rule 1168.

08/21/08